

GTA-Seam Tape

Butyl Rubber Based Sealant Tape

Description

GTA-Seam Tape is a highly adhesive elastomeric butyl rubber sealant tape developed for GEL-TECH SYSTEMS. GTA-Seam Tape is used in GTS-350 positive side and GTS-500 blind side waterproofing systems for above and below grade construction.

GTA-Seam Tape remains flexible and provides a superior watertight seal that is not affected by normal movement of buildings and structures. It is UV resistant and can withstand extreme temperatures. GTA-Seam Tape is extruded onto a release film for easy application. GTA-Seam Tape is ideal for effective, permanent waterproofing.

Uses

GTA-Seam Tape is applied in both above grade and below grade applications. GTA-Seam Tape is suitable for new construction and repair. Applications include the following types of waterproofing: horizontal positive side waterproofing (GTS-350); vertical wall positive side waterproofing (GTS-350); and blind side waterproofing (GTS-500). Areas of application include: plaza decks; elevator pits; poured wall foundations; block wall foundations; brick wall foundations; granite/limestone foundations; split slab construction; diaphragm wall (blind side); and green roofs.

Application

Surface must be clean, dry and free of oil, grease and dust. Center GTA-Seam Tape on edge of overlapping seam of GTM-16 or GTM-20 Protection Sheets. Without stretching the tape, apply over the prepared surface area. Allow GTA-Seam Tape to lay naturally. Using a seam roller, press GTA-Seam Tape firmly into place through release film. Peel off the release film from the GTA-Seam Tape.

PHYSICAL PROPERTIES – GTA-Seam Tape

Color	• Light Grey
Odor	• None
Solids Content	• 100% (ASTM D-1353)
Water Absorption	• 88% (ASTM D-570)
Bonding Time	• Instant Tack
Service Temperature	• -40°F - 180°F

Health and Safety

Follow all recommended safety guidelines when working at jobsite. Wear suitable gloves, masks, protective clothing and safety glasses. See MSDS or SDS.

Packaging

GTA-Seam Tape is manufactured in 4in. x 50ft. rolls. The rolls are packaged in cartons of 8 rolls and carton weighs approximately 65 lbs.

Storage & Shelf Life

Store in clean, dry conditions at 50 to 80° F. Shelf life is approximately 12 months, when stored according to recommended storage guidelines.

Transportation

GTA-Seam Tape is classified as a DOT non-hazardous material.

Limitations

All GEL-TECH SYSTEM components must be installed in immediate succession at time of application. After application, the installed GEL-TECH SYSTEMS must be protected from environmental exposure and preceding trades.

For Technical Assistance Contact:



RE-Systems Group Americas, Inc.
1136 114th Ln NW Suite 400
Minneapolis, MN 55447
P: 612.872.1900
F: 612.872.1902
www.re-systemsgroup.com

GTS and GEL-TECH SYSTEMS are registered trademark and patent covered products. All information and statements including test results and recommendations are believed to be truthful and accurate, however The RE-Systems Group Americas, Inc. does not warrant or guarantee anything contained in this document. Product users should verify suitability independently. RE-Systems Group Americas, Inc. MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS.